

# FMC650

PROFESSIONAL LTE CAT 1/GNSS/BLUETOOTH®  
TERMINAL

Product page



## RELIABLE GLOBAL COVERAGE AND SEPARATE GNSS MODULE

Reliable 4G connection with fallback to 2G network ensures wide-ranging coverage of your fleet management needs. This model uses a separate module to gather GNSS data and has dual-channel, L1 + L5 support.

## REMOTE DOWNLOAD OF TACHOGRAPH FILES AND LIVE DATA

Tachograph live data reading via K-Line, Tacho CAN or FMS connections for everyday driver management and fleet efficiency

## CAN DATA READING FROM HEAVY VEHICLES AND SPECIAL MACHINERY

Read J1939 data that includes standard CAN FMS from heavy vehicles like trucks and raw J1939 data from special machinery, such as construction cranes or electric buses. Possibility to connect to CAN line with multiple nodes.

## CONNECTING EXTERNAL DEVICES

2x RS232 and 1x RS485 serial communication interfaces for connecting external devices, such as thermographs, sensors, RFID readers and more



CONSTRUCTION & MINING



HEAVY DUTY TRANSPORT



PUBLIC SAFETY SERVICES



REFRIGERATED TRANSPORT



INTERNATIONAL LOGISTICS



AGRICULTURE TRANSPORT

Teltonika FMC650 is a direct successor to current most popular 4G PROFESSIONAL lineup device — FMC640. FMC650 has 4G (LTE Cat 1) network coverage including 2G (GSM) fallback compatibility. Device equipped with GNSS and LTE modules, external GNSS and LTE antennas. Separate GNSS module improves the accuracy of the track, making FMC650 more suitable for free flow electronic tolling system integration. Compared to FMC640 — FMC650 has a new processor that improves the devices computation power along with increased device internal memory it can be tailored to more specific use cases. Switchable CAN terminators that will allow you to use the device in CAN network with numerous nodes. Lastly, it can be powered via USB for easier configuration process. All the features that are supported by FMC640 is also supported by FMC650, therefore it will maximize your fleet efficiency with features like FMS CAN data (J1939), fuel CAN data (J1708), tachograph live data (K-Line), remote tachograph file download, various third party RS232 or RS485 devices support and Dual-SIM or eSIM compatibility. Terminal is suitable for applications like international logistics, refrigerated transport, agriculture, construction & mining, security & emergency services and even more.



**Product**

Model name FMC650-MBX50

**Module**

Name MeiG SLM320-PE2C

Technology LTE(Cat1)/ 2G(GSM/GPRS)

**GNSS**

Module Name Airoha AG3335MB  
 GNSS GPS, GLONASS, GALILEO, BEIDOU, QZSS  
 Receiver L1 and L5 dual-band GNSS receiver  
 Tracking sensitivity -165 dBm  
 Position accuracy < 2.5 CEP  
 Hot start 1 s  
 Warm start < 25 s  
 Cold start < 32 s

**Cellular**

Technology LTE Cat 1, GSM  
 2G bands B2/B3/B5/B8  
 4G bands LTE-FDD:B1/B3/B7/B8/B20/B28  
 LTE-TDD:B38/B40/B41  
 Data transfer LTE FDD: Max 10Mbps (DL)/Max 5Mbps (UL) LTE TDD Max 8Mbps (DL)/Max 2Mbps (UL) GPRS: Max 85.6Kbps (DL)/Max 85.6Kbps (UL)  
 Data support SMS (text/data)

**Power**

Input voltage range 8 - 32 V DC with overvoltage (compatible with pulse 5a and pulse 5b) and reverse polarity protection  
 Internal Back-up battery 550 mAh Ni-Mh, 8,4 V battery  
 2 W max. Current consumption at 12 V  
 At 12V < 4 mA (Deep Sleep)  
 At 12V < 11 mA (Online Deep Sleep)  
 At 12V < 32 mA (GPS Sleep)  
 At 12V < 45 mA (nominal with no load)  
 At 12V < 0.25 A Max. (with full Load / Peak)

2 W max.	At 24V < 2,9 mA (Deep Sleep)
Current consumption at 24 V	At 24V < 7 mA (Online Deep Sleep)
	At 24V < 17 mA (GPS Sleep)
	At 24V < 35 mA (nominal with no load)

### BLUETOOTH® technology

Name	Blue NRG232
Specification	5.0 + LE
Supported peripherals	Temperature and Humidity sensor, Universal BLUETOOTH® LE sensors support

### Physical specification

Dimension	104,1 x 76,8 x 31,5 mm (L x W x H)
Weight	197 g

### Operating environment

Operating temperature (without battery)	-40 °C to +85 °C
Storage temperature (without battery)	-40 °C to +85 °C
Operating humidity	5% to 95% non-condensing
Ingress Protection Rating	IP41
Battery storage temperature	-20 °C to +45°C

### Interface

Digital Inputs	4
Digital Outputs	4
Analog Inputs	4
1-Wire	1
RS232	2
RS485	1
CAN J1939	2
J1708	1
K-line	1
GNSS antenna	External High Gain (L1+L5)
GSM antenna	External High Gain
USB	2.0 Mini-USB — device can be powered by USB for easier device configuration
LED indication	2 status LED lights
SIM	2x SIM Card (Dual-SIM) or 1x eSIM
Memory	16 MB internal flash memory and external Micro SD card up to 32GB
Switchable CAN terminators	Supported on CAN1 and CAN2 lines

### Features

Movement detection	Accelerometer
Scenarios	Green/Eco Driving, Over Speeding detection, Jamming detection, Excessive Idling detection, Towing detection, Crash detection, Immobilizer, iButton Read Notification

Functionalities	Auto Geofencing, Manual Geofencing, Trip detection, Odometer, DDD download and Tacho online data, Offline tracking
Supported peripherals	Garmin, RFID RS232, RFID 1-Wire, iButton 1-Wire, Temperature 1-Wire, LV-CAN200, ALL-CAN300, CAN FMS (J1939, J1708), K-line data, Continental tire pressure measurement sensor, Iridium SBD (Iridium Edge/TSM232), Carrier freezer, Log Mode, NMEA, TCP ASCII/Binary, Temperature and humidity sensor, Universal BLE sensors support
Sleep modes	GPS Sleep, Online Deep Sleep, Deep Sleep
Configuration and firmware update	FOTA Web, FOTA, Teltonika Configurator
SMS	Configuration, Events, DOUT control, Debug
GPRS commands	Configuration, DOUT control, Debug
Time Synchronization	GNSS, NITZ, NTP
Fuel monitoring	LLS (Analog), Digital LLS (RS232, RS485), LV-CAN200, CAN FMS, Ultrasonic level sensor
Ignition detection	Digital Input, Accelerometer, External Power Voltage
RS485 input voltage range on A or B pin (common-mode voltage)	-7V to +12V

### Certification & Approvals

Regulatory	CE-RED, UKCA, E-mark, RCM, Pulse 5a, SIRIM QAS, ICASA, CITC
------------	---